

339.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- 12VDC based !
- Closed front !



CARTFT.COM



Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.

Celeron-M 1.7Ghz is recommended for fanless operation.

| CALU specifications   |                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher     |
| Memory                | Supports DDR 333/266 DIMM RAM<br>0.8" low profile<br>2x memory slots !<br>Maximum : 2 GB |
| Video                 | Intel Extreme Graphics 2<br>Supports up to 64MB DVTM video memory                        |
| Audio                 | Software AC '97 Audio CODEC                                                              |

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Peripheral Connection</b> | <p>Front :</p> <ul style="list-style-type: none"> <li>1 x IEEE 1394 Firewire port</li> <li>1 x USB 2.0 / 1.1 Port</li> <li>1 x MIC Port</li> <li>1 x Ear Phone output Jack</li> <li>Power-on button</li> <li>Reset button</li> <li>Power-on and HDD LED</li> </ul> <p>Rear :</p> <ul style="list-style-type: none"> <li>1 x RS232 COM port</li> <li>1 x parallel printer port</li> <li>1 x RJ45 10/100Mb Fast Ethernet</li> <li>1 x Line-Out output Jack</li> <li>2 x USB 2.0 / 1.1 Ports</li> <li>1 x 15 pin VGA</li> <li>1 x 12v DC Power Jack input</li> </ul> |
| <b>Storage</b>               | <p>One 2.5 inch Hard Disk and 9.5mm high.</p> <p>(Support Ultra DMA 33/66/100).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Weight &amp; Size</b>     | <p>System approximately 3kg (fully equipped).</p> <p>System Dimension: 155 x 255 x 55 mm</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Power req.</b>            | 12V, 5A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Accessory</b>             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Storage</b>               | Supports all 2.5" standard IDE hard drive, ATA-100/66/33.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Scope of supply</b>       | <p>110V/230V EU power supply</p> <p>Barebone</p> <p>CPU Kühlkörper</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

Graphics driver for 800x480 resolution : [Here](#)