



379.00 EUR  
incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- Integr. Autostart Controller
- Integr. Automotive power

**Support:** [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.  
Celeron-M 1.7Ghz is recommended for fanless operation.

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

| CALU specifications          |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Processor (supported)</b> | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher                                                                                                                                                                                                                                                                                                                             |
| <b>Memory</b>                | <p>Supports DDR 333/266 DIMM RAM</p> <p>0.8" low profile</p> <p>2x memory slots !</p> <p>Maximum : 2 GB</p>                                                                                                                                                                                                                                                                                                      |
| <b>Video</b>                 | <p>Intel Extreme Graphics 2</p> <p>Supports up to 64MB DVTM video memory</p>                                                                                                                                                                                                                                                                                                                                     |
| <b>Audio</b>                 | Software AC '97 Audio CODEC                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Peripheral Connection</b> | <p>Front :</p> <p>1 x IEEE 1394 Firewire port</p> <p>1 x USB 2.0 / 1.1 Port</p> <p>1 x MIC Port</p> <p>1 x Ear Phone output Jack</p> <p>Power-on button</p> <p>Reset button</p> <p>Power-on and HDD LED</p> <p>Rear :</p> <p>1 x RS232 COM port</p> <p>1 x parallel printer port</p> <p>1 x RJ45 10/100Mb Fast Ethernet</p> <p>1 x Line-Out output Jack</p> <p>2 x USB 2.0 / 1.1 Ports</p> <p>1 x 15 pin VGA</p> |

|                          |                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------|
| <b>Storage</b>           | One 2.5 inch Hard Disk and 9.5mm high.<br><br>(Support Ultra DMA 33/66/100).          |
| <b>Weight &amp; Size</b> | System approximately 3kg (fully equipped).<br><br>System Dimension: 155 x 255 x 55 mm |
| <b>Power req.</b>        | 9-16VDC, 5A                                                                           |

**Accessory**

|                        |                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Storage</b>         | Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo<br><br>Supports all 2.5" standard IDE hard drive, ATA-100/66/33. |
| <b>Scope of supply</b> | Connector cable for Plus, ignition plus and ground<br><br>Barebone<br><br>Barebone<br><br>CPU Kühlkörper                        |

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)